



Mobile Transformers - fully Plug-and-Play - Protection Category IP44

Type 100kVA

Product:

Type = 59PAxx

Description = Three phase autotransformer 50-60Hz, splash proof

- Electrical properties:
 - Upri 3x400V Y + N
 - Usec 3x230V Y + N
 - P 100kVA

- Connections:
 - Pri = 4 flexible power cables 120 mm² L1-L2-L3 N of 4 meters
 - Type H07RN-F, Equipped with a Power Lock
 - Sec = Output via 3 built-in Power Locks L1-L2-L3
 - Neutral = Output via 1 built-in Power Lock
 - PE = Via 4 meters outgoing cable and / or wing nut

- Mechanical properties :
 - Dimensions → 1050x700x900mm
 - Metal housing IP44 (RAL 7042)
 - Weight → 370kg
 - Movement possible with forklift forks and lifting eyes
 - Wheels

- Electrical protection:
 - Primary equipped with an <Automatic Circuit Breaker> type MCCB 250A





Type 160kVA

Product:

Type = 61PAxx

Description = Three phase autotransformer 50-60Hz, splash-proof

- Electrical properties:
 - Upri 3x400V Y + N
 - Usec 3x230V Y + N
 - P 160kVA

- Connections:
 - Pri = 4 flexible power cables 120 mm² L1-L2-L3 N of 4 meters
 - Type H07RN-F, Equipped with a Power Lock
 - Sec = Output via 3 built-in Power Locks L1-L2-L3
 - Neutral = Output via 1 built-in Power Lock
 - PE = Via 4 meters outgoing cable and / or wing nut

- Mechanical properties :
 - Dimensions → 1050x700x900mm
 - Metal housing IP44 (RAL 7042)
 - Weight → 450kg
 - Movement possible with forklift forks and lifting eyes

- Electrical protection:
 - Primary equipped with an <Automatic Circuit Breaker> type MCCB 400A





Type 250kVA

Product:

Type = 62PAxx

Description = Three phase autotransformer 50-60Hz, splash proof

- Electrical properties:
 - Upri 3x400V Y + N
 - Usec 3x230V Y + N
 - P 250kVA

- Connections:
 - Pri = 4 flexible power cables 150 mm² L1-L2-L3 N of 4 meters
 - type H07RN-F, Equipped with a Power Lock
 - Sec = Output via 2 series in parallel from 6 built-in Power Locks
 - L1-L2-L3
 - L1-L2-L3
 - Neutral = Output via 1 built-in Power Lock
 - PE = Via 4 meters outgoing cable and / or wing nut

- Mechanical properties :
 - Dimensions → 1050x700x900mm
 - Metal housing IP44 (RAL 7042)
 - Weight → 540kg
 - Movement possible with forklift forks and lifting eyes

- Electrical protection:
 - Primary equipped with an <Automatic Circuit Breaker> type MCCB 630A





Type 400kVA

Product:

Type = 64PAxx

Description = Three phase autotransformer 50-60Hz, splash-proof

- Electrical properties:
 - Upri 3x400V Y + N
 - Usec 3x230V Y + N
 - P 400kVA

- Connections:
 - Pri = Input via 2 series in parallel with 8 connection terminals type Power Lock
 - L1-L2-L3
 - L1-L2-L3 N PE
 - Sec = Output via 3 series in parallel of 9 built-in Power Locks
 - L1-L2-L3
 - L1-L2-L3
 - L1-L2-L3
 - Neutral = Output via 1 built-in Power Lock
 - PE = Via 4 meters outgoing cable and / or wing nut

- Mechanical properties :
 - Dimensions → 1500x1000x1000mm
 - Metal housing IP44 (RAL 7042)
 - Weight → 1000kg
 - Movement possible with forklift forks and lifting eyes

- Electrical protection:
 - Primary equipped with an <Automatic Circuit Breaker> type MCCB 1000A





50kVA

Product:

Type = 58PFxx

Description = Three phase isolation transformer 50-60Hz

- Electrical properties:
 - Upri 3x400V Δ
 - Wall socket: 63A 4P CEE
 - Including primary insurance
 - Usec 3x400V Y + N
 - Various connections including fuse
 - CEE 400V 63A 5p, CEE 400V 32A 5p, 230V 16A 3p
 - P 50kVA

- Mechanical properties
 - IP20
 - Wheels
 - Movement possible with forklift forks





7.4kVA

Product:

Type = xxECxx / IRC

Description = Mono phase protection transformer 50-60Hz – Low inrush current (IRC)

- Electrical properties:
 - Upri ...
 - Including switch
 - Usec ...
 - Including insurance
 - P ...

- Mechanical properties
 - IP20
 - Silent Blocks
 - lifting eyes

